

Description:

This is a full synthetic lubricant based on carefully selected very high quality base oils, which meets the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications, where the older Dexron II and Dexron III fluids are recommended.

Applications:

This high quality ATF can be used in automatic transmissions with torque converters of passenger cars, as well as in wet clutches and power steering units.

Performance level:

Dexron VI
Mercon LV
Aisin Warner JWS 3309/3324 (WS)
Chrysler Dodge Mopar AS68RC (Type IV)
Chrysler Dodge Mopar ATF+/-2/+3/+4
Ford Mercon /WSS-M2C138-CJ/166-H/922-A1/924-A
Honda Acura DW-1/ATF-Z1 (except for CVT)
Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
Hyundai/Kia JWS3314/9683
Isuzu Besco ATF II/III
Nissan Matic C/D/J/K/S
Jaguar ATF 3403 M115/JLM 20238
JASO M315-2013 1A/1A-LV/2A
Mazda ATF M-III/M-V
Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA
Subaru ATF/ATF 5AT/ATF HP
Suzuki ATF 3309/3314/3317/2326/2384 K
Toyota D-II/D-III/T-III/T-IV/WS



Features:

Frictional properties: very smooth gear shifting, no vibration.
Anti-wear protection: significantly extended transmission life.
Extended oil life: excellent thermal and oxidation stability

Characteristics:

Density at 15 °C, Kg/L	0,847
Viscosity 40 °C, mm ² /s	30,0
Viscosity 100 °C, mm ² /s	6,0
Viscosity Index	151
Colour	RED